

COLOUR SELECT

ECO PANEL G2 RECESSED MODULE



PRODUCT DETAILS:



- Size: 600x600, 1200x300, 1200x600
- Rated life: L70/B50 50000hrs
- LED: Colour Select via DIP Switch, CCT 4000K/5000K/6500K, CRI>80, 6 SDCM
- Beam angle: Symmetrical, 110°
- Driver: Remote, Non-Dim
- Rating: IP40 from the front, IP20 from the rear, Class II
- Operating temperature: 0°C to +40°C
- Housing: Aluminium trim, SPCC cold rolled steel back
- Finishing: White RAL9016, Powder coating
- Diffuser: Polystyrene, Frosted
- Connection: 1.3m Flex & Plug
- Accessory: Complete with restraint bracket kit
- Warranty: 5 year

MADE TO ORDER OPTIONS:

DALI/PUSH/1-10V dimming, Plaster master frames, Surface mount frames, Suspension Kit

APPLICATIONS:

Recessed, Internal
Offices, Schools, Foyers, Waiting-rooms, Shopping centres,
Commercial, Retail



CODE	DESCRIPTION	POWER [~]	LUMENS [*]	EFFICACY	WEIGHT
ECOPL066CSEG2	600X600 27W COLOUR SELECT 4000K/5000K/6500K CRI>80 NON-DIM	27W	2812lm [^]	104lm/W [^]	1.9kg
ECOPL123CSEG2	1200X300 27W COLOUR SELECT 4000K/5000K/6500K CRI>80 NON-DIM	28W	2839lm [^]	101lm/W [^]	2.0kg
ECOPL126CSEG2	1200X600 50W COLOUR SELECT 4000K/5000K/6500K CRI>80 NON DIM	49W	5023lm [^]	103lm/W [^]	4.3kg

*Delivered lumens from luminaire, including thermal, electrical and optic losses. [~]Tested system powers from luminaire. [^]@4000K.