

COLOUR SELECT

ECO PANEL GEN2

PRODUCT DETAILS

Size: 600x600mm, 1200x300mm, 1200x600mm
 Rated life: L70 B50 50000hrs
 LED: Colour Select 4000K/5000K/6500K, CRI80, 6SDCM
 Beam angle: Symmetrical, 110°
 Driver: Remote, Non dimmable
 Rating: IP40 from below/IP20 from above, Class II
 Operating temperature: 0°C to +40°C
 Housing: Aluminium trim, Steel back plate
 Finishing: White RAL9016, Powder coated
 Diffuser/Lens: Polystyrene (PS), Frosted,
 Connection: 1.2m Flex & Plug
 Accessory: Complete with restraint bracket kit
 Warranty*: 5 year





MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

Dimming, Emergency, Surface mounted frame, Recessed frame

APPLICATIONS

Recessed (grid ceiling), Internal
 Offices, Schools, Foyers, Waiting-rooms, Shopping centres,
 Commercial, Retail



VERSION	L (MM)	W (MM)	H (MM)	F (MM)
ECOPL066CSEG2	595	595	31	1200
ECOPL123CSEG2	1195	295	31	1200
ECOPL126CSEG2	1195	595	33	1200

CODE	DESCRIPTION	POWER	LUMENS	EFFICACY	WEIGHT
ECOPL066CSEG2	ECO PANEL 600X600 27W 4/5/65K @ 4K	27W	2800LM	104LM/W	1.93KG
ECOPL123CSEG2	ECO PANEL 1200X300 28W 4/5/65K @ 4K	28W	2800LM	100LM/W	2.00KG
ECOPL126CSEG2	ECO PANEL 1200X600 49W 4/5/65K @ 4K	49W	5000LM	102LM/W	4.34KG

*Please refer to the warranty policy at www.pierlite.co.nz; "POWER" is tested system powers from luminaire; "LUMENS" is delivered lumens from luminaire, including thermal, electrical and optic losses; ^Figures are interpolated / extrapolated from data at other versions.