

GIOTTO BULKHEAD GEN2

PRODUCT DETAILS




Rated life: L80 B10 60000hrs
 LED: 3000K/4000K, CRI80, 3SDCM
 Beam angle: Symmetrical
 Driver: Integral, Non-Dim/DALI dimming
 Rating: IP44, IK10, Class I
 Operating temperature: -25°C to +25°C
 Housing: Polycarbonate (PC)
 Finishing: White
 Diffuser/Lens: Polycarbonate (PC), Frosted
 Warranty: 5 year

MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

Other dimming options, Emergency (compliant to AS/NZS 2293)

APPLICATIONS

Surface mounted (ceiling), Internal/External
 Residential, Commercial spaces



CODE	DESCRIPTION	POWER [~]	LUMENS [*]	EFFICACY	WEIGHT
3034797	GIOTTO BULKHEADE GEN2 3000K CRI80 NON-DIM	23W	2111LM	92LM/W	1.2KG
3034796	GIOTTO BULKHEADE GEN2 4000K CRI80 NON-DIM	23W	2225LM	97LM/W	1.2KG
3034797DALI	GIOTTO BULKHEADE GEN2 3000K CRI80 DALI	23W	2111LM	92LM/W	1.2KG
3034796DALI	GIOTTO BULKHEADE GEN2 4000K CRI80 DALI	23W	2225LM	97LM/W	1.2KG

[~]Tested system powers from luminaire. ^{*}Delivered lumens from luminaire, including thermal, electrical and optic losses. [^]Figures are interpolated / extrapolated from data at other versions.