

START BOLLARD

PRODUCT DETAILS

Rated life: L70 B50 50000hrs
 LED: 3000K/4000K, CRI80, 5SDCM
 Beam angle: Asymmetrical, 60°
 Driver: Integral, Non-Dim
 Rating: IP65, IK10, Class I
 Operating temperature: -35°C to +50°C
 Housing: Die-cast/Extruded aluminium
 Finishing: Black RAL9005, Powder coated with special anti-corrosion treatment for coastal areas, Salt Spray testing 1000hrs (in compliance with ISO 9227 standard)
 Diffuser/Lens: Polycarbonate (PC), Frosted
 Connection: 0.25m cable with IP68 cable connector
 Accessory: Mounting base, stainless steel screws
 Warranty: 5 year





MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

500mm height

APPLICATIONS

Ground mount, External
 Coastal areas, Pedestrian areas, Public or private gardens



CODE	DESCRIPTION	POWER [~]	LUMENS [*]	EFFICACY	WEIGHT
0047941	START BOLLARD 1000MM 26W 3000K CRI80 NON-DIM	25W	1101LM	44LM/W	6.4KG
0047943	START BOLLARD 1000MM 26W 4000K CRI80 NON-DIM	26W	1095LM	42LM/W	6.4KG

[~]Tested system powers from luminaire. ^{*}Delivered lumens from luminaire, including thermal, electrical and optic losses. [^]Figures are interpolated / extrapolated from data at other versions.