


ELFOO SURFACE MOUNTED LINEAR LIGHT

PRODUCT DETAILS

Size: 1200mm, Linkable
 Rated life: L80 B10 50000hrs
 LED: 4000K, CRI80, 3SDCM
 Glare control: UGR19 design
 Beam angle: Symmetrical 80°
 Driver: Integral, DALI dimming, Flicker-Free design
 Rating: IP20, Class I
 Operating temperature: -20°C to +45°C
 Housing: Aluminium
 Finishing: Silver/White/Black, Powder coated, Black reflectors
 Diffuser/Lens: Polycarbonate (PC), Frosted
 Connection: Quick release gear tray and removable connector
 Warranty: 5 year





MADE TO ORDER OPTIONS (LEAD TIME AND MOQ MAY APPLY)

Non-Dim, Other dimming options, Casambi, Tunable white

APPLICATIONS

Surface mounted (ceiling), Internal
 Offices, Schools, Commercial interiors



VERSION	L (MM)	W (MM)	H (MM)
1200MM	1290	53	78

CODE	DESCRIPTION	POWER [~]	LUMENS [*]	EFFICACY	WEIGHT
ELFOO12840DAS	ELFOO SURFACE MOUNTED LINEAR LIGHT 30W 4000K CRI80 UGR15 DALI SILVER	30W	3327LM	111LM/W	3.8KG
ELFOO12840DAW	ELFOO SURFACE MOUNTED LINEAR LIGHT 30W 4000K CRI80 UGR15 DALI WHITE	30W	3327LM	111LM/W	3.8KG
ELFOO12840DAB	ELFOO SURFACE MOUNTED LINEAR LIGHT 30W 4000K CRI80 UGR15 DALI BLACK	30W	3327LM	111LM/W	3.8KG

[~]Tested system powers from luminaire. ^{*}Delivered lumens from luminaire, including thermal, electrical and optic losses. [^]Figures are interpolated / extrapolated from data at other versions.